

## MEMS Variable Optical Attenuator (SVOA)

<b>Features</b>	
Low insertion loss Compact size Available in both normally open and closed states	
<b>Application</b>	
Power equalization in multi-channel, optically amplified network Gain-tilt control in EDFA Dynamic Gain/Channel Equalizers/ in DWDM/CWDM networks Photoreceiver trimming Receiver protection/switch during transmitter trun-ons	

### Specifications:

Parameter	Value
Operating Wavelength (nm)	1528~1565 or 1570-1607
Attenuation Range(dB)	≤30
Inerstion Loss (dB)	≤0.8
PDL (dB)	≤0.3 (0~15dB) ≤0.5 (15-20dB)
PMD (ps)	≤0.1
Response Time (ms)	≤10
TDL (dB)	≤3.0 (0~20)
Return Loss (dB)	≥40
Operating Temperature(°C)	-5 ~+65
Fiber Type	SMF-28e
Hermeticity (Atm.cm <sup>3</sup> /s)	<10 <sup>-7</sup>
Package Dimension( mm)	φ5.5x25

### Ordering Information

SVOA	Type	Wavelength	Attenuation Range	Operating Voltage	Pigtail Type	Fiber Type	Length	Connector
	D=Dark B=Bright	1550 1590 C+L	15=15dB 20=20dB 30=30dB	5=5V 15=15V	250=250um bare fiber 900=900um loose tube	SMF-28e	1=1m	NE=None FA=FC/APC FC=FC/UPC SA=SC/APC SC=SC/UPC LC=LC/UPC LA=LC/APC MU=MU/UPC XX=Others