

## Wavelength Division Multiplexer Coupler-650/1550nm, 650/1310nm

### Specifications

Parameters	Unit	650/1550, 650/1310 WDMC
1550+/-20nm	dB	≤0.6
1310+/-20nm		
650+/-20nm	dB	≤1.5
	dB	≥15
PDL	dB	≤0.15
Directivity	dB	≥50
Return Loss	dB	≥50
Handling Power	W	1
Operating Temperature	℃	-5 ~ +70
Storage Temperature	℃	-40 ~ +85

### Package Information

Configuration	1x2, 2x2		
Fiber Length	1m, others on request		
Fiber Type	SMF-28e		
Pigtail Type	250μm Bare Fiber	900μm Loose Tube	900μm/2mm/3mm Loose Tube
Dimensions (mm)	φ3.0x54	φ3.0x54	90x16x9

### Ordering Information

**WDMC- ①-②②②②②②②②-③③③-④④④-⑤-⑥-⑦⑦-⑧⑧⑧⑧**

①	Grade	P=Grade P;
②	Wavelength	650/1550; 650/1310;
③	Port	1x2; 2x2;
④	Pigtail Type	250=250μm Fiber; 900=900μm Loose Tube; 2mm=2mm loose tube; 3mm=3mm Loose Tube;
⑤	Fiber Type	1=SMF-28e;
⑥	Length	1=1m; X=Other;
⑦	Connector	NE=None; FA=FC/APC; FC=FC/UPC; SA=SC/APC; SC=SC/UPC; LC=LC/UPC; XX=Others;
⑧	Package	3x54; 90x16x9;